



FISCHER ULTIMATE™ SERIES

**RUGGED
COMPACT
LIGHTWEIGHT**

**2 TO 42
CONTACTS**

- IP68 / IP69 / Hermetic
- 360° EMC shielding
- High corrosion resistance
- 10,000 mating cycles




Single Pair Ethernet
System Alliance



fischer[®]
CONNECTORS

Part of Conexivity Group



07 (2 – 10 contacts)

08 (2 – 9 contacts)

11 (8 – 19 contacts)

13 (5 – 27 contacts)

15 (2 – 27 contacts)

18 (42 contacts)

*Actual size 1:1 when printed at full size on A4 paper.

RESINATED CONTACT BLOCK

- Better sealing (IP68/69 even unmated, gas-tight, NBCR decontamination)
- Greater shock and vibration resistance
- Superior cable resistance (traction)

PLUGS**

CABLE MOUNTED



BODY STYLES

Locking system	Push-pull	Quick-release
Sealing	IP68/IP69	IP68/IP69
Design	Short/Overmolding	Short/Overmolding

PANEL FRONT MOUNTED



BODY STYLES

Locking system	Non-locking
Sealing	IP68/IP69
Design	Front-projecting

RECEPTACLES**

CABLE MOUNTED



BODY STYLES

Sealing	IP68 / IP69
Design	Standard

PANEL FRONT MOUNTED



BODY STYLES

Sealing	IP68/IP69 Hermetic
Design	Front-projecting

PANEL REAR MOUNTED



BODY STYLES

Sealing	IP68/IP69 Hermetic	IP68/IP69 Hermetic
Design	Front-projecting	Rear-projecting

** Available in brass and aluminum.
Available in anthracite and chrome grey finish.

BEND RELIEF & CABLE ASSEMBLY

- Bend relief for easy self-assembly, no tool required
- Cable assembly with straight or angled overmolding
- Submersible solution available on demand, 20m and more!



Download the dedicated [Technical Specifications](https://www.fischerconnectors.com/download-center)
[fischerconnectors.com/download-center](https://www.fischerconnectors.com/download-center)