

PANEL REAR MOUNTED RECEPTACLE REAR-PROJECTING


GENERAL INFORMATIONS

Part number	130290
Designation	UR02W18 F042P BK1 E1AB
Product line	UltiMate™ Series
Series size	18
Connector type	Receptacle
Body style design	Rear-projecting
Housing material	Brass
Housing color	Anthracite
Contact termination	PCB
Contact gender	Female
Contact configuration	Multipole low voltage
Locking system	Plug-related
Mounting type	Panel Rear Mounted
Cable diameter (min - max) [mm]	-
Panel cut-out diameter [mm]	25.1
Data protocol compliance	-



Picture for illustration purpose only.
Contact configuration may vary- refer to pin layout.

DIMENSIONS



KEYING CODE



PIN LAYOUT



All dimensions and images shown are in millimeters and are for reference only.

ELECTRICAL & CONTACT CONFIGURATION

Number of contacts	Contact type	Insultator material	Contact Ø [mm]	Pin Ø [mm]	Ground pin Ø [mm]	Wire size min [AWG]	Wire size max [AWG]	Test voltage AC r.m.s [kV] in mated position		Test voltage DC [kV] in mated position		Current per contact [A]
								Contact to body	Contact to contact	Contact to body	Contact to contact	
42	Multipole low voltage	PBT	0.7	0.5	0.7	-	-	1.5	1.5	2.4	2.5	3

ENVIRONMENTAL & MECHANICAL DATA

Characteristic	Value	Standard
Sealing performance	IP68/IP69 unmated	IEC 60529 (-2m/24h)
Operation temperature	From -55 °C to 135 °C	IEC 60068-2-14-Nb
Corrosion resistance	Salt mist, 1000 hours ; 5% salt solution, 35°C	IEC 60068-2-11 Test Ka // MIL-STD-202 Method 101 Condition A // EIA-364-26
Endurance	10'000	IEC 60512-9-1 // EIA-364-09
Vibration resistance	37,80 Grms	MIL-STD-202 Method 214A Condition I // EIA-364-28 Condition V
Shock resistance	300g amplitude, half sine pulse of 3 ms, no discontinuity > 1 µs	MIL-STD-202 Method 213 // EIA-364-27